






# STT & 0GK††BT

## Thyristor-Thyristor Modules

Dimensions in mm (1mm=0.0394")



Type	$V_{RSM}$	$V_{RRM}$
STT240GK30BT	3400	3000
STT240GK32BT	3600	3200
STT240GK34BT	3800	3400
STT240GK36BT	4000	3600
STT240GK38BT	4200	3800
STT240GK40BT	4400	4000
STT240GK42BT	4600	4200



Symbol	Test Conditions	Maximum Ratings	Unit
$I_{TRMS}, I_{FRMS}$ $I_{TAVM}, I_{FAVM}$	$T_{VJ}=T_{VJM}$ $T_C=85^{\circ}C$ ; 180° sine	377 240	A
$I_{TSM}, I_{FSM}$	$T_{VJ}=45^{\circ}C$ $V_R=0$ t=10ms (50Hz), sine t=8.3ms (60Hz), sine	9000 10900	A
	$T_{VJ}=T_{VJM}$ $V_R=0$ t=10ms(50Hz), sine t=8.3ms(60Hz), sine	8000 9600	
$\int i^2 dt$	$T_{VJ}=45^{\circ}C$ $V_R=0$ t=10ms (50Hz), sine t=8.3ms (60Hz), sine	470000 565000	A <sup>2</sup> s
	$T_{VJ}=T_{VJM}$ $V_R=0$ t=10ms(50Hz), sine t=8.3ms(60Hz), sine	414000 496000	
$(di/dt)_{cr}$	$T_{VJ}=T_{VJM}$ f=50Hz, $t_p=200\mu s$ $V_D=2/3V_{DRM}$ $I_G=1A$ $di_G/dt=1A/\mu s$ repetitive	150	A/ $\mu s$
	non repetitive, $I_T=I_{TAVM}$	500	
$(dv/dt)_{cr}$	$T_{VJ}=T_{VJM}$ ; $R_{GK}=\infty$ ; method 1 (linear voltage rise) $V_{DR}=2/3V_{DRM}$	1000	V/ $\mu s$
$P_{GM}$	$T_{VJ}=T_{VJM}$ $I_T=I_{TAVM}$ $t_p=30\mu s$	120	W
	$t_p=500\mu s$	60	
$P_{GAV}$		8	W
$V_{RGM}$		10	V
$T_{VJ}$ $T_{VJM}$ $T_{stg}$		-40...+140	°C
		140	
		-40...+125	
$V_{ISOL}$	50/60Hz, RMS $I_{ISOL} \leq 1mA$ t=1min	3000	V~
	t=1s	3600	
$M_d$	Mounting torque (M6)	4.5-7/40-60	Nm/lb.in.
	Terminal connection torque (M10)	11-13/97-115	
Weight	Typical	1500	g



# STT240GK\*\*BT

## Thyristor-Thyristor Modules

Symbol	Test Conditions	Characteristic Values	Unit
<b>IRRM</b>	$T_{VJ}=T_{VJM}; V_R=V_{RRM}$	50	mA
<b>V<sub>TM</sub></b>	$I_{TM}=1000A; T_{VJ}=25^{\circ}C$	3.50	V
<b>V<sub>TO</sub></b>	For power-loss calculations only ( $T_{VJ}=T_{VJM}$ )	1.560	V
<b>r<sub>T</sub></b>		2.14	mΩ
<b>V<sub>GT</sub></b>	$V_D=6V; T_{VJ}=25^{\circ}C$ $T_{VJ}=-40^{\circ}C$	3 4	V
<b>I<sub>GT</sub></b>	$V_D=6V; T_{VJ}=25^{\circ}C$ $T_{VJ}=-40^{\circ}C$	200 300	mA
<b>V<sub>GD</sub></b>	$T_{VJ}=T_{VJM}; V_D=2/3V_{DRM}$	0.25	V
<b>I<sub>GD</sub></b>	$T_{VJ}=T_{VJM}; V_D=2/3V_{DRM}$	10	mA
<b>I<sub>L</sub></b>	$T_{VJ}=25^{\circ}C; t_p=30\mu s; V_D=6V$ $I_G=1A; di_G/dt=1A/\mu s$	400	mA
<b>I<sub>H</sub></b>	$T_{VJ}=25^{\circ}C; V_D=6V; R_{GK}=\infty$	300	mA
<b>t<sub>gd</sub></b>	$T_{VJ}=25^{\circ}C; V_D=1/2V_{DRM}$ $I_G=1A; di_G/dt=1A/\mu s$	2	us
<b>t<sub>q</sub></b>	$T_{VJ}=T_{VJM}; I_T=240A; t_p=200\mu s; -di/dt=10A/\mu s$ $V_R=100V; dv/dt=50V/\mu s; V_D=2/3V_{DRM}$	250	us
<b>R<sub>thJC</sub></b>	DC current	0.0320	K/W
<b>R<sub>thJK</sub></b>	DC current	0.048	K/W
<b>ds</b>	Creeping distance on surface	12.7	mm
<b>da</b>	Creepage distance in air	9.6	mm
<b>a</b>	Maximum allowable acceleration	50	m/s <sup>2</sup>

### FEATURES

- \* International standard package
- \* Copper base plate
- \* Pressure Contact Technology
- \* BusBar Terminal
- \* Isolation voltage 3600 V~
- \* RoHS compliant

### APPLICATIONS

- \* Motor control, softstarter
- \* Power converter
- \* Heat and temperature control for industrial furnaces and chemical processes
- \* Lighting control
- \* Solid state switches

### ADVANTAGES


- \* Simple mounting
- \* Improved temperature and power cycling
- \* Reduced protection circuits




# STT240GK\*\*BT

## Thyristor-Thyristor Modules


Maximum On-State Forward Voltage Drop  
( $T_J = 125\text{ C}$ )




Maximum Transient Thermal Impedance  
(Junction to Case)




Maximum On-State Power Dissipation  
(Sinusoidal Waveform)



Maximum Allowable Case Temperature  
(Sinusoidal Waveform)



Maximum On-State Power Dissipation  
(Rectangular Waveform)



Maximum Allowable Case Temperature  
(Rectangular Waveform)

