



HUR30120

Soft Recovery Behaviour High-Performance Wide Temperature Range Ultra Fast Recovery Epitaxial Diodes



A=Anode, C=Cathode, TAB=Cathode

Dimensions TO-247AC



Dim.	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	19.81	20.32	0.780	0.800
B	20.80	21.46	0.819	0.845
C	15.75	16.26	0.620	0.640
ØD	3.15	3.65	0.124	0.144
E	4.32	5.49	0.170	0.216
F	5.40	6.30	0.213	0.248
G	1.65	2.13	0.065	0.084
H	3.80	4.50	0.150	0.177
J	1.00	1.40	0.039	0.055
K	10.80	11.10	0.425	0.437
L	4.70	5.30	0.185	0.209
M	0.40	0.80	0.016	0.031
N	1.50	2.49	0.059	0.098



	V _{RSM}	V _{RRM}
	V	V
HUR30120	1200	1200

Symbol	Test Conditions	Maximum Ratings	Unit
I _{FRMS}	T _C =115°C; rectangular, d=0.5	70	A
I _{FAVM}		30	
I _{FSM}	T _{VJ} =45°C; t _p =10ms (50Hz), sine	210	A
E _{AS}	T _{VJ} =25°C; non-repetitive; I _{AS} =11.5A; L=180uH	14	mJ
I _{AR}	V _A =1.25·V _R typ.; f=10kHz; repetitive	1.2	A
T _{VJ}		-55...+175	°C
T _{VJM}		175	
T _{stg}		-55...+150	
P _{tot}	T _C =25°C	165	W
M _d	mounting torque	0.8...1.2	Nm
Weight	typical	6	g

HUR30120

Soft Recovery Behaviour High-Performance Wide Temperature Range Ultra Fast Recovery Epitaxial Diodes




Fig. 1 Forward current I_F versus V_F




Fig. 2 Reverse recovery charge Q_r versus $-di_F/dt$




Fig. 3 Peak reverse current I_{RM} versus $-di_F/dt$




Fig. 4 Dynamic parameters Q_r , I_{RM} versus T_{VJ}




Fig. 5 Recovery time t_{tr} versus $-di_F/dt$




Fig. 6 Peak forward voltage V_{FR} and t_{tr} versus di_F/dt




Fig. 7 Transient thermal resistance junction to case

Constants for Z_{thjC} calculation ..A:

i	$R_{thi}(K/W)$	t_i (s)
1	0.465	0.0052
2	0.179	0.0003
3	0.256	0.0397

Constants for Z_{thjC} calculation ..AR:

i	$R_{thi}(K/W)$	t_i (s)
1	0.368	0.0052
2	0.1417	0.0003
3	0.0295	0.0004
4	0.5604	0.0092